

WMR Purchasing Group

ADDENDUM

Addendum Number: 0001-2018 Addendum 2
Issued: June 15, 2018 by: Barry Feller

**SUPPLY AND DELIVERY OF TWO FIRE PUMPER APPARATUSES AND
ONE PUMPER TANKER APPARATUS
Bid # 0001-2018**

URGENT

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID OPPORTUNITY AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS.

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in **Form A: Bid Submission Paragraph A1.7** may render your Bid non-responsive.

PART A – BID SUBMISSION

- Acknowledge and list *0001-2018 Addendum 2*

The following is a summary of changes incorporated in the replacement Bid Submission:

| Part – Section – Item | Changes – <u>Underlined</u> text signifies alteration from the original specification text. |
|---|---|
| PART E – PUMPER APPARATUS DETAILED SPECIFICATIONS E3 CAB E3.18 | Revise: E3.18 to read: A Canadian flag design shall be painted <u>or applied as a graphic</u> on the cab grille. |
| PART E – PUMPER APPARATUS E3 CAB E3.36 | Revise: E3.36 to read: All wiring shall be placed in metal raceways <u>or concealed in a minimum of loom. All cab and body wiring to be concealed. No open or loose wiring permitted.</u> |
| PART E – PUMPER APPARATUS E5 BUMPERS E5.2 | Revise: E5.2 to read: The bumper shall be extended a minimum of 18in. to a maximum <u>21in.</u> from the face of the cab as required. |
| PART E – PUMPER APPARATUS E12 ENGINES & TRANSMISSIONS E12.1 | Revise: E12.1 to read: The vehicle shall utilize a Cummins ISL or <u>L9</u> Diesel engine providing a minimum of 400 horsepower. |

| Part – Section – Item | Changes – <u>Underlined</u> text signifies alteration from the original specification text. |
|--|---|
| <p>PART E – PUMPER APPARATUS</p> <p>E14 ENGINE COOLING</p> <p>E14.1</p> | <p>Revise: E14.1 to read:</p> <p><u>Silicone</u> hose shall be used for all engine coolant lines with stainless steel constant torques hose clamps. All radiator hoses should be routed, loomed, and secured so as to provide maximum protection from chafing, crushing, or contact with other moving parts.</p> |
| <p>PART E – PUMPER APPARATUS</p> <p>E18 CHASSIS</p> <p>E18.4</p> | <p>Revise: E18.4 to read:</p> <p>A tow bar shall be provided under the tail board at the centre of the truck or frame <u>mounted tow hooks rated for the weight of the vehicle when it is at maximum capacity.</u></p> |
| <p>PART E – PUMPER APPARATUS</p> <p>E29 DOORS</p> <p>E29.1</p> | <p>Revise: E29.1 to read:</p> <p>R-O-M Corporation <u>or Amdor</u> roll up doors with anodized satin finish shall be provided on all exterior body compartment doors located around and behind apparatus water tank, not transverse storage compartment.</p> |